



3300 SERIES 8-CHANNEL NVR

Enjoy the ease of plug-and-play IP recording with this 8-channel NVR

- + Plug-and-play support for Alibi IP cameras (Up to 8.0 megapixel resolution)
- + Supports up to 8.0 megapixel recording resolution
- + Integrated 8-port PoE network switch with 802.3af/at support
- + Built-in PoE switch automatically detects and displays Alibi IP cameras plugged into the switch
- + Linux embedded operating system
- + 4K HDMI and VGA video outputs
- + Supports H.265, H.264, and H.264 OVC video compression
- + Multiple selectable recording modes (schedule, continuous, motion detection and event)
- + Recording features: event search, event log, and email and event notification
- + Free iOS/Android app available
- + Features Alibi Power Tools, a collection of powerful utilities designed to streamline and simplify the installation, set-up, and management of your Alibi surveillance system
- + Central Management Software (CMS) manages up to 256 devices across multiple locations from a single platform

What's included:

- + 3300 Series 8-Channel NVR
- + USB mouse
- + 100-240 Vac power cord
- + 6' HDMI cable
- + 6' CAT5e patch cable
- + Quick Start Guide



ALIBI SWITCHBOX NVR

3300 Series 8-Channel NVR

SPECIFICATIONS

SPECIFICATIONS

Number of Channels Supported	8
Compression Format	Supports H.265, H.264, H.264 OVC
Recording Performance	80 Mbps max
Remote Viewing Output Capacity	160 Mbps max
Supported Frame Rate per Channel	Main stream: Up to 60 fps, Sub-stream: Up to 60 fps
Recording Type	Continuous, Schedule, Event, Motion Detection, VCA
Supported IP Camera Resolution	8MP/6MP/5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Supported Playback Resolution	8MP/6MP/5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Decoding Capability	2-ch @ 4K, or 8-ch @ 1080p
Synchronous Playback	2-ch @ 4K, or 8-ch @ 1080p
Video Output	VGA, HDMI
HDMI Video Output Formats	4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA Video Output Formats	1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Two-Way Audio Input	1-ch, RCA (2.0 Vp-p, 1kΩ)
Audio Output	1-ch, RCA (Linear, 1kΩ)
Export Formats	.MP4
Ethernet	1x Gigabit RJ-45 self-adaptive Ethernet interface, 8 independent 10 /100 Mbps PoE Ethernet interfaces
Power Over Ethernet	≤ 120 W, Supported Standards: 802.3af and 802.3at
USB	1x USB 2.0, 1x USB 3.0
Hard Drive Interface	2x SATA
Hard Drive Capacity	2x HDDs max, up to 8TB capacity
Alarm Input	4x (rear panel), Camera Dependent
Alarm Output	1x (rear panel), Camera Dependent
Operating System	Embedded Linux
Security	Password Protection
Protocols	IPv4, TCP/IP, UDP, HTTP, UPnP, RTSP/RTP/RTCP, SMTP, FTP, DHCP, NTP, DNS, ONVIF, HTTP multipart
Power Requirements	100 - 240 Vac
Power Consumption	≤ 15W (without HDD)
Weight	6.6 lbs. (without HDD)
Dimensions (in.)	15" W × 11.4" D × 1.8" H
Operating Temperature	14°F - 131°F
Color / Material	Black
Material	Aluminum
Approvals	CE, FCC, RoHS,UL

REMOTE CLIENT SYSTEM REQUIREMENTS

Operating System	Microsoft Windows XP, Vista, 7, 8, 10 (32-bit and 64-bit version) / Apple MacOS X 10.5 (Intel x86 only), 10.6 and 10.7
Web Browser	Microsoft Internet Explorer 8.0, 9.0, 10, and 11 (32-bit version), Mozilla Firefox 13 and higher and 3.6, Safari 5 and higher
Software Requirements	Web Component Installation
Mobile Client OS Platform	iOS, Android (Alibi Witness)

SUPPLIED ACCESSORIES

Quickstart Guide, USB Mouse, 110 Vac Power Cord, Hard Drive Cables and Screws